



Hillpos

Direct Thermal Barcode Printer

HDT-410

- High quality double-walled clamshell design
- 203 dpi resolution models
- Head-up sensor
- USB 2.0
- 8MB SDRAM, 8 MB Flash



HDT-410

Direct Thermal Barcode Printer



Model	HDT-410
Resolution	203 DPI
Print method	Direct Thermal
Print speed	152mm(6'')/s Max.
Max.print width	108 mm (4.25")
Max.print length	1778 mm (70")

Media	
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	20 ~ 118 mm (0.78 " ~ 4.6 ")
Media thickness	0.06 ~ 0.25 mm (2.36 ~ 9.8 mil)
Media core diameter	25.4~76.2 mm (1"~3")
Label length	10~1778 mm (0.39"~70")
Label roll capacity	127 mm (5") OD (External diameter)

Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4Gb
Interface	USB+Serial+Lan

Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128, subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
2D barcode	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0°, 90°, 180°, 270°
Emulation	TSPL, EPL, ZPL, DPL

Physical Features	
Dimension	235.62 × 207.5 × 165.5 mm (W×H×D)
Weight	1.58 kg

Reliability	
Warranty	One year
Print head	30 km

Software	
Driver	Windows / Linux / Mac / Android
SDK	Windows / Android / iOS

Power supply	
Input	AC 100~240V
Output	DC 24V, 2.5A, 60W

Options	
Factory Options	① Serial ② WIFI ③ Bluetooth ④ Peeling machine
Dealer Options	① External paper roll holder and 1 "paper roll ② Extension board for external paper roll holder ③ Shipment waybill box

Environmental Conditions	
Operation	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% non-condensing
Storage environment	-40 ~ 60°C(-40~140°F), Humidity:10 ~ 90% non-condensing

